



# TIMBAL

Surface mounted fixtures with symmetrical light distribution. Wall fixtures with light emission on one or two sides.

Cylindrical design available in 2 sizes: 180mm and 235mm.

Protection rating against dust and moisture: entire IP65. Protection rating for resistance to harmful mechanical impacts: IK07.

Robust body and trim made of die-cast aluminium treated against corrosion and coated with polyester powder painting available in various colour finishes, customized RAL under request.

High-purity aluminium reflectors in various finishes depending on the beam angle outcome. Top reflector: faceted metalized or sandblasted anodised depending on the beam angle outcome. Bottom reflector: sandblasted.

5mm tempered protection glass clear as standard.

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Built-in driver, included.

Passive temperature management: heat dissipation through the fixture body itself and an interior aluminium heat sink.

Mounting to the wall through mounting plate with two fixing holes. Cable entry from the mounting plate.

**Suggested applications:** façades, patios, porches and similar installations.



ø 180mm

± 228mm

26° 39° 77° 112°



1850lm - 3690lm

11W - 24W



ø 235mm

± 258mm

13°/16° 24°/27° 36°/38° 96°/97° 109°



1850lm - 5560lm

11W - 36W



ø 180mm

± 460mm

26° 39° 77° 112°



(2x) 1850lm - (2x) 3690lm

(2x) 11W - (2x) 24W



ø 235mm

± 520mm

13°/16° 24°/27° 36°/38° 96°/97° 109°



(2x) 1850lm - (2x) 5560lm


(2x) 11W - (2x) 36W

## ELECTRONIC EQUIPMENT

Standard.

DALI/DSI/switchDIM/corridorFUNCTION.

## ACCESSORIES AND FINISHES



more product details



rovasi.com